

C class

Product Information
GHC631IX

MODEL	GHC631IX
Energy efficiency classes of domestic range hoods (A-G)	C
Annual Energy Consumption - AEC hood (kWh/a)	31.6
Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	E
Lighting Efficiency classes (A-G)	C
The Grease Filtering Efficiency classes (A-G)	C
Sound power level L WA - (dB)	65
Time increase factor - f	1.6
Fluid Dynamic Efficiency - FDE hood	10.1
Energy Efficiency Index - EEI hood	71
Measured air flow rate at best efficiency point - Q BEP (m ³ /h)	111
Measured air pressure at best efficiency point P BEP (Pa)	160.8
Measured electric power input at best efficiency point - W BEP (W)	49.1
Nominal power of the lighting system - W L (W)	4
Average illumination of the lighting system on the cooking surface - E middle (lux)	72
Lighting Efficiency LE hood - (lux/Watt)	18
Grease Filtering Efficiency GFE hood - (%)	78
Minimum airflow (Q min)	150
Maximum air flow - Q max (m ³ /h)	230
Airflow -boost (Q boost)	-
Minimum sound power level L WA - (dB)	45dB
Maximum sound power level L WA - (dB)	65dB
Sound power level-boost L WA - (dB)	-
Measured power consumption off mode P o (W)	0
Measured power consumption in standby mode - P s (W)	0

Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "